



Harmonised Product Standard

EN 14351-1:2006+A2:2016

Declaration of Performance

Type of construction product:

Entrance doors and Patio doors

DOVISTA uPVC

Door Rebated, double-glazed

DOP nr.:

D-uPVC-Rebated-DGU-20260730

The performance of the Entrance doors and Patio doors in the product line DOVISTA uPVC Door Rebated, double-glazed are in conformity with the performances declared on the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.

System of assessment and verification of constancy of performance of the construction product:
(AVCP) System 3

Intended use:

For domestic and commercial buildings

Manufacturer:

DOVISTA A/S

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):

NB 0766 eph Dresden, Germany

NB 2797 - BSI Group The Netherlands B.V., NL

Name of authorized representative: DOVISTA (UK) Ltd., VAT No. GB 493346816, Mr Henrik Kjeldsen

Address, Authorized representative: Ground Floor, THE FORUM, 9 Lancaster Way, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU +44 01480 759511


Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

Signed on behalf of DOVISTA A/S

30 jul 2026

Horsens


Allan Lindhard Jørgensen
CEO, DOVISTA A/S

Declaration of Performance

DOVISTA uPVC; Door Rebated, double-glazed

D-uPVC-Rebated-DGU-20260730

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
Opening function								
EDRI Rebated door, inward opening, 1-leaf								
Declared value	Class B3 (1200 Pa)	Class 3A (100 Pa)	None	N/A	NPD	1,30 (W/m2K)	Gg 0,63 / LTg 0,81	Class 3 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2000	-	-	-	-	-	EN 12207:2017
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	EN 673:2024/EN 410:2011	EN 1026:2016
Notified body	NB 0766	NB 0766	-	-	-	NB 2797	-	NB 0766
Test report	2625258-01	2625258-01	-	-	-	-	-	2625258-01
Tested size (mm), WxH	1670 x 2264	1670 x 2264	-	-	-	1538 x 2725	-	1670 x 2264
EDRI-2 Rebated door, inward opening, 2-leaf								
Declared value	Class C3 (1200 Pa)	Class 3A (100 Pa)	None	N/A	NPD	1,33 (W/m2K)	Gg 0,63 / LTg 0,81	Class 3 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2000	-	-	-	-	-	EN 12207:2017
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	EN 673:2024/EN 410:2011	EN 1026:2016
Notified body	NB 0766	NB 0766	-	-	-	NB 2797	-	NB 0766
Test report	2625258-03	2625258-03	-	-	-	-	-	2625258-03
Tested size (mm), WxH	1801 x 2264	1801 x 2264	-	-	-	2500 X 2725	-	1801 x 2264
EDRO Rebated door, outward opening, 1-leaf								
Declared value	Class B3 (1200 Pa)	Class 3A (100 Pa)	None	N/A	NPD	1,30 (W/m2K)	Gg 0,63 / LTg 0,81	Class 3 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2000	-	-	-	-	-	EN 12207:2017
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	EN 673:2024/EN 410:2011	EN 1026:2016
Notified body	NB 0766	NB 0766	-	-	-	NB 2797	-	NB 0766
Test report	2625258-01	2625258-01	-	-	-	-	-	2625258-01
Tested size (mm), WxH	1670 x 2264	1670 x 2264	-	-	-	1538 x 2725	-	1670 x 2264

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

Copyright DOVISTA A/S

** Declared values see sheet "4.11, Acoustic performance"

Opening function	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
EDRO-2	Rebated door, outward opening, 2-leaf							
Declared value	Class C3 (1200 Pa)	Class 3A (100 Pa)	None	N/A	NPD	1,33 (W/m2K)	Gg 0,63 / LTg 0,81	Class 3 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2000	-	-	-	-	-	EN 12207:2017
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	EN 673:2024/EN 410:2011	EN 1026:2016
Notified body	NB 0766	NB 0766	-	-	-	NB 2797	-	NB 0766
Test report	2625258-03	2625258-03	-	-	-	-	-	2625258-03
Tested size (mm), WxH	1801 x 2264	1801 x 2264	-	-	-	2500 X 2725	-	1801 x 2264

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S