



Harmonised Product Standard

**EN 14351-1:2006+A2:2016**

**Declaration of Performance**

Type of construction product:  
Facade windows and Casement doors

**DOVISTA uPVC**  
**Window Rebated, double-glazed**

DOP nr.:  
**W-uPVC-Rebated-DGU-20260730**

The performance of the Facade windows and Casement doors in the product line DOVISTA uPVC Window Rebated, double-glazed are in conformity with the performances declared on the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.

System of assessment and verification of constancy of performance of the construction product:  
(AVCP) System 3

Intended use:  
For domestic and commercial buildings

Manufacturer:  
**DOVISTA A/S**

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):

NB 2797 - BSI Group The Netherlands B.V., NL  
NB 2189 - MLTB Sp. z o.o., PL

Name of authorized representative: DOVISTA (UK) Ltd., VAT No. GB 493346816, Mr Henrik Kjeldsen  
Address, Authorized representative: Ground Floor, THE FORUM, 9 Lancaster Way, Ermine Business Park,  
Huntingdon, Cambridgeshire, PE29 6XU +44 01480 759511

Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.


Date:

Signed on behalf of DOVISTA A/S

30 jul 2026

---

Horsens



---

Allan Lindhard Jørgensen  
CEO, DOVISTA A/S

Declaration of Performance

DOVISTA uPVC; Window Rebated, double-glazed

W-uPVC-Rebated-DGU-20260730

|                         | 4.2<br>Resistance to<br>windload | 4.5<br>Water tightness | 4.6<br>Dangerous<br>substances | 4.8<br>Load bearing capacity<br>of safety devices | 4.11<br>Acoustic<br>performance | 4.12<br>* Thermal<br>transmittance<br>coefficient | 4.13<br>* Radiation<br>properties | 4.14<br>Air permeability |
|-------------------------|----------------------------------|------------------------|--------------------------------|---------------------------------------------------|---------------------------------|---------------------------------------------------|-----------------------------------|--------------------------|
| Opening function        |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| FLFixed light           |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value          | Class 5 (2000 Pa)                | Class 9A (600 Pa)      | None                           | N/A                                               | NPD                             | 1,33 (W/m2K)                                      | Gg 0,63 / LTg 0,81                | Class 3 (±600 Pa)        |
| Classification standard | EN 12210:2016                    | EN 12208:2000          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2017            |
| Test standard           | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | EN 673:2024/EN 410:2011           | EN 1026:2016             |
| Notified body           | NB 2797                          | NB 2797                | -                              | -                                                 | -                               | NB 2797                                           | -                                 | NB 2797                  |
| Test report             | KM 13358                         | KM 13358               | -                              | -                                                 | -                               | -                                                 | -                                 | KM 13358                 |
| Tested size (mm), WxH   | 2400 x 2400                      | 2400 x 2400            | -                              | -                                                 | -                               | 1538 x 1480                                       | -                                 | 2400 x 2400              |
| SHOSidehung window      |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value          | Class C3 (1200 Pa)               | Class 9A (600 Pa)      | None                           | N/A                                               | NPD                             | 1,33 (W/m2K)                                      | Gg 0,63 / LTg 0,81                | Class 4 (±600 Pa)        |
| Classification standard | EN 12210:2016                    | EN 12208:2001          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2017            |
| Test standard           | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | EN 673:2024/EN 410:2011           | EN 1026:2016             |
| Notified body           | NB 2189                          | NB 2189                | -                              | -                                                 | -                               | NB 2797                                           | -                                 | NB 2189                  |
| Test report             | MLTB-5816                        | MLTB-5816              | -                              | -                                                 | -                               | -                                                 | -                                 | MLTB-5816                |
| Tested size (mm), WxH   | 2247 x 1328                      | 2247 x 1328            | -                              | -                                                 | -                               | 1538 x 1480                                       | -                                 | 2247 x 1328              |
| THOTophung window       |                                  |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value          | Class C3 (1200 Pa)               | Class 9A (600 Pa)      | None                           | N/A                                               | NPD                             | 1,33 (W/m2K)                                      | Gg 0,63 / LTg 0,81                | Class 4 (±600 Pa)        |
| Classification standard | EN 12210:2016                    | EN 12208:2001          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2017            |
| Test standard           | EN 12211:2016                    | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | EN 673:2024/EN 410:2011           | EN 1026:2016             |
| Notified body           | NB 2189                          | NB 2189                | -                              | -                                                 | -                               | NB 2797                                           | -                                 | NB 2189                  |
| Test report             | MLTB-5815                        | MLTB-5815              | -                              | -                                                 | -                               | -                                                 | -                                 | MLTB-5815                |
| Tested size (mm), WxH   | 1787 x 1268                      | 1787 x 1268            | -                              | -                                                 | -                               | 1538 x 1480                                       | -                                 | 1787 x 1268              |

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

\*\* Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S

| Opening function        | 4.2<br>Resistance to<br>windload     | 4.5<br>Water tightness | 4.6<br>Dangerous<br>substances | 4.8<br>Load bearing capacity<br>of safety devices | 4.11<br>Acoustic<br>performance | 4.12<br>* Thermal<br>transmittance<br>coefficient | 4.13<br>* Radiation<br>properties | 4.14<br>Air permeability |
|-------------------------|--------------------------------------|------------------------|--------------------------------|---------------------------------------------------|---------------------------------|---------------------------------------------------|-----------------------------------|--------------------------|
| TITU                    | Tilt and turn window, inward opening |                        |                                |                                                   |                                 |                                                   |                                   |                          |
| Declared value          | Class 3 (1200 Pa)                    | Class 8A               | None                           | N/A                                               | NPD                             | 1,31 (W/m2K)                                      | Gg 0,63 / LTg 0,81                | Class 4 (±600 Pa)        |
| Classification standard | EN 12210:2016                        | EN 12208:2001          | -                              | -                                                 | -                               | -                                                 | -                                 | EN 12207:2017            |
| Test standard           | EN 12211:2016                        | EN 1027:2016           | -                              | -                                                 | -                               | EN ISO 10077-2: 2003/2012                         | EN 673:2024/EN 410:2011           | EN 1026:2016             |
| Notified body           | NB 2797                              | NB 2189                | -                              | -                                                 | -                               | NB 2797                                           | -                                 | NB 2189                  |
| Test report             | KM 76189                             | MLTB-5808              | -                              | -                                                 | -                               | -                                                 | -                                 | MLTB-5808                |
| Tested size (mm), WxH   | 1288 x 1588                          | 2495 x 2413            | -                              | -                                                 | -                               | 1538 x 1480                                       | -                                 | 2495 x 2413              |

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

\*\* Declared values see sheet "4.11, Acoustic performance"

Copyright DOVISTA A/S